



LEGS & CASTERS
CASTERS

IEC Non-Hooded Casters

These *light-duty black nylon non-hooded twin-wheel casters* are available with a 5/16-18 thread or a square top plate.

Most sizes are available with a brake option (-BR), which stops the wheels from rolling. IL700-15-5-STM caster has a 5/16 dia. grip neck stem, 1-1/2" long, and comes with a socket for wood.



IL700 thru IL706 PLATE CASTER



IL700 thru IL705 THREADED CASTER



IL702 WIDE WHEEL CASTER

CASTERS - IL700 SERIES

CASTERS	WHEEL DIA.	PLATE / TH'D. STEM SIZE	LOAD RATING (LB)
IL700-15-PLT	1-1/2	1-1/2 SQ	20
IL700-15-5-STM	1-1/2	5/16 x 1-1/2 STEM	20
IL701-15-PLT	1-1/2	1-1/2 SQ	50
IL701-15-5X3/4	1-1/2	5/16-18 x 3/4	50
IL702-15X2-PLT	1-1/2 x 2 WIDE	1-1/2 SQ	100
IL702-15X2-PLT-BR	1-1/2 x 2 WIDE	1-1/2 SQ	100
IL703-2-PLT	2	1-1/2 SQ	75
IL703-2-PLT-BR	2	1-1/2 SQ	75
IL703-2-5X3/4	2	5/16-18 x 3/4	75
IL703-2-5X3/4-BR	2	5/16-18 x 3/4	75
IL704-2-PLT	2	1-1/2 SQ	100
IL704-2-PLT-BR	2	1-1/2 SQ	100
IL704-2-51	2	5/16-18 x 1	100
IL704-2-51-BR	2	5/16-18 x 1	100
IL704-3-PLT	3	1-1/2 SQ	150
IL705-3-PLT-BR	3	1-1/2 SQ	150
IL705-3-51	3	5/16-18 x 1	150
IL705-3-51-BR	3	5/16-18 x 1	150
IL706-4-PLT	4	2-3/8 SQ	225
IL706-4-PLT-BR	4	2-3/8 SQ	225

CASTER ATTACHMENT OPTIONS

TOP PLATE



THREADED



STEM



5/16" DIA. STEM & SOCKET



3/4" U-CLIP





IEC 2" Hooded Casters without Wheel Brakes

These *light-duty, black nylon hooded twin-wheel casters* are available in two wheel sizes (2" and 2-3/8") and with three hood types: black nylon, chrome finish or brass finish.

They are available with many top mounting options:

1/4-20, 5/16-18 or 3/8-16 thread.
1-1/2" square top plate (3/16" hole centered 1" apart).

5/16" dia., 7/16 dia., or 3/8" dia. grip neck stem (5/16" dia. comes with a socket for wood).

U-clip to fit 3/4" wide board. Most sizes are available with a brake option (-BR), which stops the wheels from rolling.

The overall height with the top plate is 2-1/2" for the 2" wheel and 3" for the 2-3/8" wheel.

The mounting height with the threaded stem or grip ring is 2-1/4" for the 2" wheel and 2-3/4" for the 2-3/8" wheel.

NOTE: See next page for caster models with wheel brakes.



IL710 BLACK CASTER
W/O BRAKE



IL710 CHROME CASTER
w/ U-CLIP



IL711 BRASS CASTER

2" CASTERS - IL710 SERIES (W/O WHEEL BRAKES)

CASTERS	WHEEL DIA.	PLATE / TH'D. STEM SIZE	LOAD RATING (LB)
IL710-2-PLT-BLK	2	1-1/2 SQ	75
IL710-2-PLT-BRS	2	1-1/2 SQ	75
IL710-2-PLT-CHR	2	1-1/2 SQ	75
IL710-2-4X1/2-BLK	2	1/4-20 x 1/2	75
IL710-2-4X1/2-BRS	2	1/4-20 x 1/2	75
IL710-2-4X1/2-CHR	2	1/4-20 x 1/2	75
IL710-2-41-BLK	2	1/4-20 x 1	75
IL710-2-41-BRS	2	1/4-20 x 1	75
IL710-2-41-CHR	2	1/4-20 x 1	75
IL710-2-5X3/4-BLK	2	5/16-18 x 3/4	75
IL710-2-5X3/4-BRS	2	5/16-18 x 3/4	75
IL710-2-5X3/4-CHR	2	5/16-18 x 3/4	75
IL710-2-51-BLK	2	5/16-18 x 1	75
IL710-2-51-BRS	2	5/16-18 x 1	75
IL710-2-51-CHR	2	5/16-18 x 1	75
IL710-2-5X1-1/2-BLK	2	5/16-18 x 1-1/2	75
IL710-2-5X1-1/2-BRS	2	5/16-18 x 1-1/2	75
IL710-2-5X1-1/2-CHR	2	5/16-18 x 1-1/2	75
IL710-2-61-BLK	2	3/8-16 x 1	75
IL710-2-61-BRS	2	3/8-16 x 1	75
IL710-2-61-CHR	2	3/8-16 x 1	75
IL710-2-5-STM-BLK	2	5/16 x 1-1/2 STEM	75
IL710-2-5-STM-BRS	2	5/16 x 1-1/2 STEM	75
IL710-2-5-STM-CHR	2	5/16 x 1-1/2 STEM	75
IL710-2-5A-STM-BLK	2	7/16 x 7/8 STEM	75
IL710-2-5A-STM-BRS	2	7/16 x 7/8 STEM	75
IL710-2-5A-STM-CHR	2	7/16 x 7/8 STEM	75
IL710-2-5B-STM-BLK	2	7/16 x 1-3/8 STEM	75
IL710-2-5B-STM-BRS	2	7/16 x 1-3/8 STEM	75
IL710-2-5B-STM-CHR	2	7/16 x 1-3/8 STEM	75
IL710-2-6-STM-BLK	2	3/8 x 1 STEM	75
IL710-2-6-STM-BRS	2	3/8 x 1 STEM	75
IL710-2-6-STM-CHR	2	3/8 x 1 STEM	75
IL710-2-U-BLK	2	3/4 U-CLIP	75
IL710-2-U-BRS	2	3/4 U-CLIP	75
IL710-2-U-CHR	2	3/4 U-CLIP	75



IEC 2" Hooded Casters with Wheel Brakes

These *light-duty, black nylon hooded twin-wheel casters* are available in two wheel sizes (2" and 2-3/8") and with three hood types: black nylon, chrome finish or brass finish.

They are available with many top mounting options:

1/4-20, 5/16-18 or 3/8-16 thread. 1-1/2" square top plate (3/16" hole centered 1" apart). 5/16" dia., 7/16 dia., or 3/8" dia. grip neck stem (5/16" dia. comes with a socket for wood). U-clip to fit 3/4" wide board. Most sizes available with a brake option (-BR), which stops the wheels from rolling.

The overall height with the top plate is 2-1/2" for the 2" wheel and 3" for the 2-3/8" wheel. The mounting height with the threaded stem or grip ring is 2-1/4" for the 2" wheel and 2-3/4" for the 2-3/8" wheel.

NOTE: All casters featured on this page have a wheel brake.



IL711 BRASS CASTER W/ BRAKE



IL711 BLACK CASTER



IL711 CHROME CASTER w/ U-CLIP & BRAKE

2" CASTERS - IL711 SERIES (WITH WHEEL BRAKES)

PART NUMBER	WHEEL DIA.	PLATE / TH'D. STEM SIZE	LOAD RATING (LB)
IL711-2-PLT-BLK-BR	2	1-1/2 SQ	75
IL711-2-PLT-BRS-BR	2	1-1/2 SQ	75
IL711-2-PLT-CHR-BR	2	1-1/2 SQ	75
IL711-2-4X1/2-BLK-BR	2	1/4-20 x 1/2	75
IL711-2-4X1/2-BRS-BR	2	1/4-20 x 1/2	75
IL711-2-4X1/2-CHR-BR	2	1/4-20 x 1/2	75
IL711-2-41-BLK-BR	2	1/4-20 x 1	75
IL711-2-41-BRS-BR	2	1/4-20 x 1	75
IL711-2-41-CHR-BR	2	1/4-20 x 1	75
IL711-2-5X3/4-BLK-BR	2	5/16-18 x 3/4	75
IL711-2-5X3/4-BRS-BR	2	5/16-18 x 3/4	75
IL711-2-5X3/4-CHR-BR	2	5/16-18 x 3/4	75
IL711-2-51-BLK-BR	2	5/16-18 x 1	75
IL711-2-51-BRS-BR	2	5/16-18 x 1	75
IL711-2-51-CHR-BR	2	5/16-18 x 1	75
IL711-2-5X1-1/2-BLK-BR	2	5/16-18 x 1-1/2	75
IL711-2-5X1-1/2-BRS-BR	2	5/16-18 x 1-1/2	75
IL711-2-5X1-1/2-CHR-BR	2	5/16-18 x 1-1/2	75
IL711-2-61-BLK-BR	2	3/8-16 x 1	75
IL711-2-61-BRS-BR	2	3/8-16 x 1	75
IL711-2-61-CHR-BR	2	3/8-16 x 1	75
IL711-2-5-STM-BLK-BR	2	5/16 x 1-1/2 STEM	75
IL711-2-5-STM-BRS-BR	2	5/16 x 1-1/2 STEM	75
IL711-2-5-STM-CHR-BR	2	5/16 x 1-1/2 STEM	75
IL711-2-5A-STM-BLK-BR	2	7/16 x 7/8 STEM	75
IL711-2-5A-STM-BRS-BR	2	7/16 x 7/8 STEM	75
IL711-2-5A-STM-CHR-BR	2	7/16 x 7/8 STEM	75
IL711-2-5B-STM-BLK-BR	2	7/16 x 1-3/8 STEM	75
IL711-2-5B-STM-BRS-BR	2	7/16 x 1-3/8 STEM	75
IL711-2-5B-STM-CHR-BR	2	7/16 x 1-3/8 STEM	75
IL711-2-6-STM-BLK-BR	2	3/8 x 1 STEM	75
IL711-2-6-STM-BRS-BR	2	3/8 x 1 STEM	75
IL711-2-6-STM-CHR-BR	2	3/8 x 1 STEM	75
IL711-2-U-BLK-BR	2	3/4 U-CLIP	75
IL711-2-U-BRS-BR	2	3/4 U-CLIP	75
IL711-2-U-CHR-BR	2	3/4 U-CLIP	75



IEC 2-3/8" Hooded Casters without Wheel Brakes

These *light-duty, black nylon hooded twin-wheel casters* are available in two wheel sizes (2" and 2-3/8") and with three hood types: black nylon, chrome finish or brass finish.

They are available with many top mounting options:

1/4-20, 5/16-18 or 3/8-16 thread.
 1-1/2" square top plate (3/16" hole centered 1" apart).
 5/16" dia., 7/16 dia., or 3/8" dia. grip neck stem (5/16" dia. comes with a socket for wood).
 U-clip to fit 3/4" wide board.
 Most sizes are available with a brake option (-BR), which stops the wheels from rolling.

The overall height with the top plate is 2-1/2" for the 2" wheel and 3" for the 2-3/8" wheel.
 The mounting height with the threaded stem or grip ring is 2-1/4" for the 2" wheel and 2-3/4" for the 2-3/8" wheel.

NOTE: Casters featured on this page do not have a wheel brake.



IL712 BLACK CASTER
W/O BRAKE



IL712 CHROME CASTER
w/ U-CLIP



IL712 BRASS CASTER

2-3/8" CASTERS - IL712 SERIES (W/O WHEELBRAKES)

PART NUMBER	WHEEL DIA.	PLATE / TH'D. STEM SIZE	LOAD RATING (LB)
IL712-2-PLT-BLK	2-3/8	1-1/2 SQ	100
IL712-2-PLT-BRS	2-3/8	1-1/2 SQ	100
IL712-2-PLT-CHR	2-3/8	1-1/2 SQ	100
IL712-2-4X1/2-BLK	2-3/8	1/4-20 x 1/2	100
IL712-2-4X1/2-BRS	2-3/8	1/4-20 x 1/2	100
IL712-2-4X1/2-CHR	2-3/8	1/4-20 x 1/2	100
IL712-2-41-BLK	2-3/8	1/4-20 x 1	100
IL712-2-41-BRS	2-3/8	1/4-20 x 1	100
IL712-2-41-CHR	2-3/8	1/4-20 x 1	100
IL712-2-5X3/4-BLK	2-3/8	5/16-18 x 3/4	100
IL712-2-5X3/4-BRS	2-3/8	5/16-18 x 3/4	100
IL712-2-5X3/4-CHR	2-3/8	5/16-18 x 3/4	100
IL712-2-51-BLK	2-3/8	5/16-18 x 1	100
IL712-2-51-BRS	2-3/8	5/16-18 x 1	100
IL712-2-51-CHR	2-3/8	5/16-18 x 1	100
IL712-2-5X1-1/2-BLK	2-3/8	5/16-18 x 1-1/2	100
IL712-2-5X1-1/2-BRS	2-3/8	5/16-18 x 1-1/2	100
IL712-2-5X1-1/2-CHR	2-3/8	5/16-18 x 1-1/2	100
IL712-2-61-BLK	2-3/8	3/8-16 x 1	100
IL712-2-61-BRS	2-3/8	3/8-16 x 1	100
IL712-2-61-CHR	2-3/8	3/8-16 x 1	100
IL712-2-5-STM-BLK	2-3/8	5/16 x 1-1/2 STEM	100
IL712-2-5-STM-BRS	2-3/8	5/16 x 1-1/2 STEM	100
IL712-2-5-STM-CHR	2-3/8	5/16 x 1-1/2 STEM	100
IL712-2-5A-STM-BLK	2-3/8	7/16 x 7/8 STEM	100
IL712-2-5A-STM-BRS	2-3/8	7/16 x 7/8 STEM	100
IL712-2-5A-STM-CHR	2-3/8	7/16 x 7/8 STEM	100
IL712-2-5B-STM-BLK	2-3/8	7/16 x 1-3/8 STEM	100
IL712-2-5B-STM-BRS	2-3/8	7/16 x 1-3/8 STEM	100
IL712-2-5B-STM-CHR	2-3/8	7/16 x 1-3/8 STEM	100
IL712-2-6-STM-BLK	2-3/8	3/8 x 1 STEM	100
IL712-2-6-STM-BRS	2-3/8	3/8 x 1 STEM	100
IL712-2-6-STM-CHR	2-3/8	3/8 x 1 STEM	100
IL712-2-U-BLK	2-3/8	3/4 U-CLIP	100
IL712-2-U-BRS	2-3/8	3/4 U-CLIP	100
IL712-2-U-CHR	2-3/8	3/4 U-CLIP	100



IEC 2-3/8" Casters with Wheel Brakes

These *light-duty, black nylon hooded twin-wheel casters* are available in two wheel sizes (2" and 2-3/8") and with three hood types: black nylon, chrome finish or brass finish.

They are available with many top mounting options:

1/4-20, 5/16-18 or 3/8-16 thread.
 1-1/2" square top plate (3/16" hole centered 1" apart).
 5/16" dia., 7/16 dia., or 3/8" dia. grip neck stem (5/16" dia. comes with a socket for wood).
 U-clip to fit 3/4" wide board.
 Most sizes are available with a brake option (-BR), which stops the wheels from rolling.

The overall height with the top plate is 2-1/2" for the 2" wheel and 3" for the 2-3/8" wheel. The mounting height with the threaded stem or grip ring is 2-1/4" for the 2" wheel and 2-3/4" for the 2-3/8" wheel.

NOTE: All casters featured on this page have a wheel brake.



IL713 BRASS CASTER W/ BRAKE



IL713 BLACK CASTER



IL713 CHROME CASTER w/ U-CLIP & BRAKE

2-3/8" CASTERS - IL713 SERIES (WITH WHEEL BRAKES)

PART NUMBER	WHEEL DIA.	PLATE / TH'D. STEM SIZE	LOAD RATING (LB)
IL713-2-PLT-BLK-BR	2-3/8	1-1/2 SQ	100
IL713-2-PLT-BRS-BR	2-3/8	1-1/2 SQ	100
IL713-2-PLT-CHR-BR	2-3/8	1-1/2 SQ	100
IL713-2-4X1/2-BLK-BR	2-3/8	1/4-20 x 1/2	100
IL713-2-4X1/2-BRS-BR	2-3/8	1/4-20 x 1/2	100
IL713-2-4X1/2-CHR-BR	2-3/8	1/4-20 x 1/2	100
IL713-2-41-BLK-BR	2-3/8	1/4-20 x 1	100
IL713-2-41-BRS-BR	2-3/8	1/4-20 x 1	100
IL713-2-41-CHR-BR	2-3/8	1/4-20 x 1	100
IL713-2-5X3/4-BLK-BR	2-3/8	5/16-18 x 3/4	100
IL713-2-5X3/4-BRS-BR	2-3/8	5/16-18 x 3/4	100
IL713-2-5X3/4-CHR-BR	2-3/8	5/16-18 x 3/4	100
IL713-2-51-BLK-BR	2-3/8	5/16-18 x 1	100
IL713-2-51-BRS-BR	2-3/8	5/16-18 x 1	100
IL713-2-51-CHR-BR	2-3/8	5/16-18 x 1	100
IL713-2-5X1-1/2-BLK-BR	2-3/8	5/16-18 x 1-1/2	100
IL713-2-5X1-1/2-BRS-BR	2-3/8	5/16-18 x 1-1/2	100
IL713-2-5X1-1/2-CHR-BR	2-3/8	5/16-18 x 1-1/2	100
IL713-2-61-BLK-BR	2-3/8	3/8-16 x 1	100
IL713-2-61-BRS-BR	2-3/8	3/8-16 x 1	100
IL713-2-61-CHR-BR	2-3/8	3/8-16 x 1	100
IL713-2-5-STM-BLK-BR	2-3/8	5/16 x 1-1/2 STEM	100
IL713-2-5-STM-BRS-BR	2-3/8	5/16 x 1-1/2 STEM	100
IL713-2-5-STM-CHR-BR	2-3/8	5/16 x 1-1/2 STEM	100
IL713-2-5A-STM-BLK-BR	2-3/8	7/16 x 7/8 STEM	100
IL713-2-5A-STM-BRS-BR	2-3/8	7/16 x 7/8 STEM	100
IL713-2-5A-STM-CHR-BR	2-3/8	7/16 x 7/8 STEM	100
IL713-2-5B-STM-BLK-BR	2-3/8	7/16 x 1-3/8 STEM	100
IL713-2-5B-STM-BRS-BR	2-3/8	7/16 x 1-3/8 STEM	100
IL713-2-5B-STM-CHR-BR	2-3/8	7/16 x 1-3/8 STEM	100
IL713-2-6-STM-BLK-BR	2-3/8	3/8 x 1 STEM	100
IL713-2-6-STM-BRS-BR	2-3/8	3/8 x 1 STEM	100
IL713-2-6-STM-CHR-BR	2-3/8	3/8 x 1 STEM	100
IL713-2-U-BLK-BR	2-3/8	3/4 U-CLIP	100
IL713-2-U-BRS-BR	2-3/8	3/4 U-CLIP	100
IL713-2-U-CHR-BR	2-3/8	3/4 U-CLIP	100