



SLANT BASE SOCKET LEVELERS


The IEC *Slant Base Socket Leveler* is ideal for heavy-duty loads where a stud is not required. Integrated ball and swivel socket provide a low-friction support interface. Ideal for cabinets, instruments, machinery and equipment.

Features

- Solid steel/stainless steel
- Integrated ball and socket
- Adjustable height
- Base adjusts 15° off centerline
- Standard gold irridite zinc finish
- Black chromate or clear chromate options
- Rubber pad or non-marring delrin base

Applications

- Equipment benches
- Machinery
- Instruments
- Enclosures



STEEL & STAINLESS STEEL

Steel	SS	Load	A	B	C	D	E
IL1-4G	IL5-4	1400	1/4-20	1/2	45/64	1	5/32
IL1-4GF	IL5-4F	1400	1/4-28	1/2	45/64	1	5/32
IL1-6G	IL5-6	3000	3/8-16	5/8	7/8	1-1/4	3/16
IL1-6GF	IL5-6F	3000	3/8-24	5/8	7/8	1-1/4	3/16
IL1-7G	IL5-7	5500	1/2-13	3/4	1-1/8	1-7/8	1/4
IL1-7GF	IL5-7F	5500	1/2-20	3/4	1-1/8	1-7/8	1/4
IL1-8G	IL5-8	6000	5/8-11	7/8	1-1/4	2-1/2	5/16
IL1-8GF	IL5-8F	6000	5/8-18	7/8	1-1/4	2-1/2	5/16
IL1-9G	IL5-9	8000	3/4-10	1-1/16	1-1/2	3	1/2
IL1-9GF	IL5-9F	8000	3/4-16	1-1/16	1-1/2	3	1/2
IL1-10G	IL5-10	20000	1-8	1-1/2	1-7/8	4	13/32
IL1-10GF	IL5-10F	20000	1-12	1-1/2	1-7/8	4	13/32

STEEL & STAINLESS STEEL WITH RUBBER PAD

Steel	SS	Load	A	B	C	D	E
IL1-4G-P	IL5-4-P	1050	1/4-20	1/2	53/64	1	5/32
IL1-4GF-P	IL5-4F-P	1050	1/4-28	1/2	53/64	1	5/32
IL1-6G-P	IL5-6-P	2250	3/8-16	5/8	1	1-1/4	3/16
IL1-6GF-P	IL5-6F-P	2250	3/8-24	5/8	1	1-1/4	3/16
IL1-7G-P	IL5-7-P	3750	1/2-13	3/4	1-1/4	1-7/8	1/4
IL1-7GF-P	IL5-7F-P	3750	1/2-20	3/4	1-1/4	1-7/8	1/4
IL1-8G-P	IL5-8-P	4500	5/8-11	7/8	1-3/8	2-1/2	5/16
IL1-8GF-P	IL5-8F-P	4500	5/8-18	7/8	1-3/8	2-1/2	5/16
IL1-9G-P	IL5-9-P	6000	3/4-10	1-1/16	1-5/8	3	1/2
IL1-9GF-P	IL5-9F-P	6000	3/4-16	1-1/16	1-5/8	3	1/2
IL1-10G-P	IL5-10-P	15000	1-8	1-1/2	2	4	13/32
IL1-10GF-P	IL5-10F-P	15000	1-12	1-1/2	2	4	13/32



INTERNATIONAL EQUIPMENT COMPONENTS, INC.
 Phone: 562.597.4533 eMail: sales@iec-corp.com
 Web: www.levelingmounts.com & www.iec-corp.com

HEAVY-DUTY LEVELERS

SLANT BASE SOCKET - DELRIN

SLANT BASE SOCKET LEVELERS


The IEC *Slant Delrin® Base Socket Leveler* is ideal for heavy-duty loads where a stud is not required. Integrated ball and swivel socket provide a low-friction support interface. Ideal for cabinets, instruments, machinery and equipment.

Features

- Solid steel/stainless steel
- Integrated ball and socket
- Adjustable height
- Base adjusts 15° off centerline
- Standard gold irridite zinc finish
- Black chromate or clear chromate options
- Non-marring delrin base

Applications

- Equipment benches
- Machinery
- Instruments
- Enclosures



DELRIN BASE - STEEL & STAINLESS STEEL

Steel	SS	Load	A	B	C	D	E
IL3-4W	IL3-4S	200	1/4-20	1/2	45/64	1	5/32
IL3-6W	IL3-6S	300	3/8-16	5/8	7/8	1-1/4	3/16
IL3-7W	IL3-7S	700	1/2-13	3/4	1-1/8	1-7/8	1/4
IL3-8W	IL3-8S	1200	5/8-11	7/8	1-1/4	2-1/2	5/16
IL3-9W	IL3-9S	1800	3/4-10	1-1/16	1-1/2	3	1/2
IL3-10W	IL3-10S	2400	1-8	1-1/2	1-7/8	4	13/32

The delrin® base is white.



SLANT BASE METRIC SOCKET LEVELERS



The IEC *Slant Base Metric Socket Leveler* is ideal for heavy-duty loads where a stud is not required. Integrated ball and swivel socket provide a low-friction support interface. Ideal for cabinets, instruments, machinery and equipment.

Features

- Solid steel/stainless steel
- Integrated ball and socket
- Adjustable height
- Base adjusts 15° off centerline
- Standard gold irridite zinc finish
- Black chromate or clear chromate options
- Rubber pad or non-marring delrin base

Applications

- Equipment benches
- Machinery
- Instruments
- Enclosures



METRIC STEEL & STAINLESS STEEL

Steel	SS	Load	A	B	C	D	E
IL1-M6G	IL5-M6	1400	M6x1	1/2	45/64	1	5/32
IL1-M10G	IL5-M10	3000	M10x1.50	5/8	7/8	1-1/4	3/16
IL1-M12G	IL5-M12	5500	M12x1.75	3/4	1-1/8	1-7/8	1/4
IL1-M16G	IL5-M16	6000	M16x2.00	7/8	1-1/4	2-1/2	5/16
IL1-M20G	IL5-M20	8000	M20x2.50	1-1/16	1-1/2	3	1/2
IL1-M24G	IL5-M24	20000	M24x3.00	1-1/2	1-7/8	4	13/32

METRIC STEEL & STAINLESS STEEL WITH RUBBER PAD

Steel	SS	Load	A	B	C	D	E
IL1-M6G-P	IL5-M6-P	1050	M6x1	1/2	53/64	1	5/32
IL1-M10G-P	IL5-M10-P	2250	M10x1.50	5/8	1	1-1/4	3/16
IL1-M12G-P	IL5-M12-P	3750	M12x1.75	3/4	1-1/4	1-7/8	1/4
IL1-M16G-P	IL5-M16-P	4500	M16x2.00	7/8	1-3/8	2-1/2	5/16
IL1-M20G-P	IL5-M20-P	6000	M20x2.50	1-1/16	1-5/8	3	1/2
IL1-M24G-P	IL5-M24-P	15000	M24x3.00	1-1/2	2	4	13/32

DELRIN BASE - METRIC STEEL & STAINLESS STEEL

Steel	SS	Load	A	B	C	D	E
IL3-M6W	IL3-M6S	200	M6x1	1/2	45/64	1	5/32
IL3-M10W	IL3-M10S	300	M10x1.50	5/8	7/8	1-1/4	3/16
IL3-M12W	IL3-M12S	700	M12x1.75	3/4	1-1/8	1-7/8	1/4
IL3-M16W	IL3-M16S	1200	M16x2.00	7/8	1-1/4	2-1/2	5/16
IL3-M20W	IL3-M20S	1800	M20x2.50	1-1/16	1-1/2	3	1/2
IL3-M24W	IL3-M24S	2400	M24x3.00	1-1/2	1-7/8	4	13/32

The delrin® base is white.